

# SCREWDRIVERS

## Clutch type mechanism (adjustable)



YD-400SCA



RR-02SC



RR-06SC



YD-5PHCA



RR-02SP



RR-06SP

| Type      | Brand  | Square hex drive | Bolt capacity mm | Model    | RPM   | Torque Nm | Air-cons. l/s | Weight kg | Inlet-thread | Hose-diameter mm | Vibration m/s <sup>2</sup> | Noise-level dB(A) |
|-----------|--------|------------------|------------------|----------|-------|-----------|---------------|-----------|--------------|------------------|----------------------------|-------------------|
| YD-400SCA | YOKOTA | 1/4" Hex         | 4                | Straight | 1.700 | 1 - 3,2   | 2,5           | 0,56      | PT 1/8"      | 6,5              | 4                          | 77                |
| RR-02SC   | RR     | 1/4" Hex         | 5                | Straight | 1.800 | 1 - 6     | 10,0          | 1,2       | PT 1/4"      | 10               | 1,6                        | 85                |
| RR-06SC   | RR     | 1/4" Hex         | 6                | Straight | 800   | 5 - 16    | 10,0          | 1,4       | PT 1/4"      | 10               | 1,6                        | 85                |
| YD-5PHCA  | YOKOTA | 1/4" Hex         | 5                | Pistol   | 1.650 | 1 - 6,6   | 5,8           | 1,2       | PT 1/4"      | 6,5              | 2                          | 77                |
| RR-02SP   | RR     | 1/4" Hex         | 5                | Pistol   | 1.800 | 1 - 6     | 10,0          | 1,3       | PT 1/4"      | 10               | 1,6                        | 85                |
| RR-06SP   | RR     | 1/4" Hex         | 6                | Pistol   | 800   | 5 - 16    | 10,0          | 1,4       | PT 1/4"      | 10               | 3,5                        | 83                |

| DIMENSIONS | Type  | A mm | B mm | C mm |
|------------|-------|------|------|------|
|            | YD-3A | 168  | 13,5 | -    |
| YD-4A      | 180   | 16   | -    |      |
| YD-5A      | 200   | 19   | -    |      |
| YD-5PHCA   | 217   | 20   | 154  |      |
| YD-40PZ    | 107   | 18   | 125  |      |
| YD-400SCA  | 209   | 16,5 | -    |      |
| YD-600SZ   | 206   | 23   | -    |      |
| YD-670A-RF | 149   | 22   | 167  |      |

  

| Type              | A mm | B mm | C mm |
|-------------------|------|------|------|
| MID-600           | 149  | 22   | 161  |
| RR-02SP / RR-06SP | 214  | 21   | 155  |
| RR-06SC           | 227  | 21   | -    |
| RR-02SC           | 260  | 21   | -    |
| RR-0800DD         | 190  | 21   | 165  |
| RR-1800DD         | 175  | 21   | 165  |

  
  

All screwdrivers adapt 1/4" standard type hexagon insert bits and are reversible..

| CONTROL | 1-Hammer   |            | Direct drive  |               |
|---------|------------|------------|---------------|---------------|
|         | YD-3A      | Push start | RR-0800DD     | Trigger start |
| YD-4A   | Push start | RR-1800DD  | Trigger start |               |
| YD-5A   | Push start |            |               |               |

  

| 2-Hammer   |                | Slip clutch (adjustable) |                |
|------------|----------------|--------------------------|----------------|
| MID-600    | Trigger start  | YD-400SCA                | Push start     |
| YD-40PZ    | 2-step trigger | YD-5PHCA                 | 2-step trigger |
| YD-600SZ   | Lever start    | RR-02SP/RR-06SP          | Trigger start  |
| YD-670A-RF | 2-step trigger | RR-02SC/RR-06SC          | Lever start    |

| ACCESSORIES               |   |                            |
|---------------------------|---|----------------------------|
| Side handles              |   |                            |
| Type                      |   | Order number               |
| RR-06SP                   | * | 75-725139-0001S<br>+822340 |
| * Supplied as standard    |   |                            |
| Hose set noise suppressor |   |                            |
| Type                      |   | Order number               |
| RR-0800DD                 |   | EH-701SUB                  |
| RR-1800DD                 |   |                            |
| RR-02SP                   |   |                            |
| RR-06SP                   |   |                            |

### Torque springs

Automotive models RR-02SP/SC and RR-06SP/SC are supplied with 2 torque springs.

### Screw spanner

The YD-400SCA and YD-5PHCA are supplied with screw spanner 2201-0243-00-00.

### Spring balancers

The performance of the tool will be increased by good balance and reduced operator fatigue, when using a spring balancer (see page 69).