

RRI-BIM SERIES



High tightening speed combined with high accuracy. No reaction forces during the tightening process. No tightening functionality when battery charge is low, thus process safety improves. Very well suited in areas where cables and hoses impede handling flexibility of tools, such as interiors of cars, coaches and trains.

Characteristics:


- Brushless motor
- 18 Volt Lithium-Ion battery (choice for 2,0 Ah or 4,0 Ah capacity)
- LED status indicates: Reverse, OK, NOK, Battery low
- Torque adjustable
- Fine-tuning on hardness of the joint, electronically
- Non-contact trigger with 2 steps
- Run-down speed up to 4.500 RPM



Battery, charger, programmer and power cord have to be ordered separately.



Type	Square/ Hex drive	Torque Nm	RPM	Weight kg	Dimensions	
					A mm	B mm
RRI-BIM15AT	1/4" Hex	7-15	4.500	1,16	29	227
RRI-BIM15T	3/8" Square	8-15	4.500	1,16	29	224
RRI-BIM25AT	1/4" hex	14-23	4.500	1,18	29	237
RRI-BIM25T	3/8" Square	15-25	4.500	1,18	29	234
RRI-BIM35T	3/8" Square	22-35	3.500	1,36	29	234
RRI-BIM45T	3/8" Square	32-45	3.500	1,42	29	244



CHARACTERISTICS

- Advanced and stable shut off system
- Brushless motor
- LED-indication OK/NOK
- LED light
- Non-contact trigger with 2 steps
- Mini USB, connector (for connecting programmer)
- Ergonomic handle design
- LI-ION battery

ACCESSORIES

- Rubber protection cover
- Aluminium cover
- Service Kit

Rubber protection cover	
RRI-BIM15T (AT)	order no. C16PW-15
RRI-BIM25T (AT)	order no. C16PW-25
RRI-BIM35T	order no. C16PW-25
RRI-BIM45T	order no. C16PW-45

Aluminium cover	
RRI-BIM serie	order no. B10PW15

Service Kits:	
RRI-BIM15T (AT)	order no. 140RK
RRI-BIM25T (AT)	order no. 170RK
RRI-BIM35T	order no. 170RK
RRI-BIM45T	order no. 180RK-YO