



AD3-DRY adaptor included



## DM52D - DRY DRILLING

- Compact & lightweight - dry core drilling only
- Highly efficient 1800W motor
- 2 speed gearbox with slow start
- Up to 182 mm diameter dry cores - hand held or rig mounted drilling
- Through spindle dust extraction system
- Switchable soft percussion - reducing heat/wear on the core improving dust extraction
- 2-in-1 spindle - 1¼" UNC (M), ½" BSP (F)
- AD3-DRY Adaptor included - ½" BSP (M) to ½" BSP (M) for use with guide rod
- Internal management system controls amount of power applied
- Front in-line handle for control
- Horizontal spirit level for alignment
- 60 mm collar for rig mounting option
- Oil bath gearbox
- Brushed motor



Supplied in A Hard Plastic Carry Case

### TECHNICAL DATA

Voltage  
 Input Power  
 Max Core Diameter  
 Collar Diameter  
 No-Load Speeds  
 Rated Load Speeds  
 Weight  
 Dimensions  
 Vibration Level  
 EAV / ELV / Exposure Points (P/H)  
 Decibel Level  
 Plug Type  
 Cord Length

### DM52D

110-120V ~ 50-60Hz  
 110-120V : 1800W  
 182 mm  
 60 mm  
 1800 (#1), 3600 (#2)  
 1080 (#1), 2160 (#2)  
 5.0 kg  
 505 mm x 105 mm x 210 mm  
 1.71 m/s<sup>2</sup>  
 EAV - 17 hrs 6 mins · ELV - >24H · EP/H 6  
 97.0 dB (A)  
 16 amp - 3.3 KVA Transformer  
 3m